



Dräger X-zone 5800 Area Monitor

State-of-the-art area monitoring – the Dräger X-zone 5800 in combination with the Dräger X-am 5000, 5100 or 5600 gas detection instruments can be used for the measurement of up to six gases. The internal pump and continuous power supply in the explosive area of Zone 0 extend the range of applications in mobile gas detection technology.

Dräger X-zone 5800



Dräger X-zone 5800



Quick guide

Connection for continuous power supply in EX Areas

Connection switching relay/
RS 485 communication

Connection charging socket/
RS 485 communication

D-211262-2020

Benefits

Area monitor

- combination with Dräger X-am 5000, 5100 or 5600 – measurement of up to 6 gases
- extensive area monitoring thanks to fenceline of up to 25 devices
- option for permanent power supply in explosive areas (Zone 0)

Innovative area monitoring

The Dräger X-zone 5800 transforms the Dräger personal gas detection instruments X-am 5000, 5100 and 5600 into innovative area monitoring devices for a wide range of applications. A outstanding combination for increased safety – in addition to the personal air monitors carried on the body, these area monitors are positioned where gas hazards are expected.

Extended area monitoring

The explosion-protected gateway Dräger ConHub transmits measured values and alarms from the Dräger X-zone 5x00 area monitor via a Modbus cable as well as data from up to 20 Dräger X-am 2800/5800 and Pac devices with Bluetooth® function to the Dräger Gas Detection Connect cloud solution. This gives you deeper insight into areas at risk while ensuring more efficient use of your fleet and increased safety of your facility.

Clear warning

Even from a distance, the illuminated green LED ring indicates that the air is free of toxic and combustible gases. Upon detection of gas hazards, the LED color changes from green to red, thus providing a clear visual warning that gas is present. Additionally, a loud and highly audible evacuation alarm is emitted. The Dräger X-zone 5800 gas entry location permits gas to diffuse into the Dräger X-am 5000, 5100 or 5600 from all sides.

Wireless fenceline

Up to 25 Dräger X-zone 5800 can be automatically interconnected to form a wireless fenceline. The interconnection of the area monitoring devices allows for rapid establishment of safety networks for larger areas.

A Dräger X-zone 5800 detecting a gas alarm transmits the alarm signal to all interconnected units. A red flashing master alarm in the unit detecting the gas contrasts with red/green flashing alarms of the connected units. This provides simple recognition of alarm status and the actual location of the hazard.

With the corresponding configuration, the maximum gas concentration in the monitored area is shown on the display. Combined with the display of the X-zone ID a clear containment of the hazard area is possible.

Continuous operation for up to 120 hours

The 24 Ah battery of the Dräger X-zone 5800 provides up to 120 hours of continuous operation – up to a complete working week.

The Power Supply Ex is available for continuous use of the X-zone 5800. It offers a 164 ft (or 50 m) supply from a safe area to a potentially explosive area and is even approved for use with the X-zone 5800 in Zone 0.

For safe transport, the cable of the Power Supply Ex is rolled up on a cable drum in which the power supply is also integrated.

Benefits

Pump or diffusion mode – suitable for your respective application

The X-zone 5800 offers you both the possibility to draw in gas from a distance of up to 98 ft (or 30 m) in pump mode and the use in diffusion mode. The switch between these two options takes less than a minute. Simply exchange the pump cover or the supplied diffusion cover against each other. The X-zone 5800 is ready for another measuring operation – without any tools.

Other benefits

- 360°-gas entry
- Approval for Ex-Zone 0
- individually configurable with the Dräger CC-Vision PC software (e.g. alarm frequency)
- inductive charging station: easy and convenient non-contact charging (outside the Ex-area)

Interfaces

The interfaces on the back of the device offer the possibility of switching actuators in case of alarms by means of the configurable relay. The interface can also directly forward device data, such as measured values of sensors and alarms, via Modbus protocol. This allows you to integrate the devices into existing evaluation units.

System Components

D-21278-2020



Power Supply Ex

The Power Supply Ex enables the X-zone 5800 to be continuously supplied with power even within an explosion-proof area.

D-14325-2017



Dräger X-am 5000

The Dräger X-am 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

D-31721-2011



Dräger X-am 5100

For manufacturing petrochemical products, aseptic packing, or handling of rocket fuel: the Dräger X-am 5100 portable single-gas detector ensures that you use the safest methods possible for handling HF, HCl, H₂O₂ or hydrazine – thanks to proven Dräger sensor technology and a device design which is perfectly customised to reactive gases.

D-23637-2009



Dräger X-am 5600

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of flammable and toxic gases and vapors as well as oxygen.

System Components

D-12779-2023



Dräger ConHub

Automated area monitoring gives you maximum safety with a minimal workload. The explosion-proof Dräger ConHub serves as a gateway that automatically connects your Dräger gas detectors from any location to Dräger Gas Detection Connect, our live monitoring solution. This helps you monitor vulnerable areas more closely, so you get the most out of your gas detection system, while also improving safety at your location.

Accessories

D-23626-2009



Bump test adapter

For function tests

D-27768-2009



Alarm damper

For use within bump tests

Accessories

D-23631-2009



Socket

For measurements of light gases

D-23634-2009



Induction charger for X-zone 5500/5800

Allowing easy charging

D-1568-2010



Plug-in charger

100 V - 240 V

D-10391-2009



Float probe

With 5 m or 16.4 ft. FKM hose

Accessories

D-1571-2010



Hose set

Consisting of water trap, dust and water filter

D-30746-2015



Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

D-0494-2018



Calibration gas and accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration gas options are easily available.

Related Products

D-6491-2017



Dräger X-am 8000

Clearance measurement was never this easy and convenient: The 1 to 7 gas detector detects toxic and flammable gases as well as vapours and oxygen all at once – either in pump or diffusion mode. Innovative signalling design and handy assistant functions ensure complete safety throughout the process.

Technical Data

Dräger X-zone 5800

Dimensions (W x H x D)	490 x 300 x 300 mm 20 x 12 x 12 in.	
Weight	10 kg (22 lbs.) (24 Ah battery)	
Ambient conditions	Temperature: -20 °C - max. +50 °C / -4 °F - max. +122 °F Pressure: 700 to 1,300 hPa Humidity: 10 to 95 % r.h.	
Ingress Protection	IP67	
Alarm	Visual 360° LED (illuminated ring) Audible 360°; >108 dB in a distance of 1 m (3 ft.), 120 dB in a distance of 30 cm (1 ft.) Configurable alarm patterns, frequencies and volumes	
Life signal	Green status display (360°), illuminated ring (LED)	
Operating time	Approx. 120 h (24 Ah battery) Depending on sensor equipment / configuration of the life signal	
Charging time	Approx. 14 h Flexible power supply: External 100 – 240 V charger (worldwide) or inductive wireless charger	
Pump operation	Maximum hose length: 45 m (150 ft.), 30 m (100 ft.) for zone 0	
Alarm output	Potential-free alarm contact for intrinsically safe circuits (6-pole); <20 V to 0.25 A (0.15 A constant current); Resisting load	
Radio transmission	Worldwide license-free ISM frequencies Digital radio, robust and interference-free transmission up to 100 m (328 ft.)	
RF approvals	915 MHz (USA, Canada, Australia),	
Approvals	ATEX	I M1 Ex ia I Ma II 1G Ex ia IIC T4 Ga
	IECEx	Ex ia I Ma Ex ia IIC T4 Ga

Power Supply Ex

Dimensions	14 x 13 x 9.8 in (or 365 x 320 x 250 mm)	
Weight	22 lbs (or 10 kg)	
Protection class	IP 44	
Approvals	ATEX	II (1)G [Ex ia Ga] IIC
	IEC Ex	[Ex ia Ga] IIC
	CSA/US	pending
Temperature range	-4 to 122 F (or -20 to 50 C)	
Cable length	Cable drum -4 to 122 F (or -20 to 50 C) Connection cable fix 0.5 m + Power Cord US	

Ordering Information

Dräger X-zone 5800	Part-No.
Dräger X-zone 5800 915 MHz, 24 Ah, pump	8329040
Bump test adapter X-zone 5x00	8323314
Alarm damper	8320110
Socket (elevated stand), 25 cm high (12 in.)	8320645
Set: cover for Dräger X-am 5100 for X-zone (diffusion only) NOT for outdoor use	8323938

Power Supply ex-approved area	
Power Supply Ex 110 V w/o power cord	8329010
Power cord USA	8329049

Charging accessories

Inductive charger with power supply:	
For USA, Japan	8322076
Plug-in charger	8320749

Pump accessories

Float probe with 5 m or 16.4 ft. FKM hose	8318371
Hose set (consisting of water trap, dust and water filter)	8321527
Hose, electronically conductive	1180681
FKM hose, solvent-resistant	1203150
Tygon® hose	8320766

Tygon® is a registered trademark of Saint-Gobain Corporation.

Ordering Information

Communication accessories

Dräger CC-Vision

www.draeger.com/software

USB DIRA with USB cable

8317409

Gateway

Dräger ConHub

3729600

Notes

Notes

Notes

Not all products, features, or services are for sale in all countries. Trademarks mentioned herein are the property of its respective owner. Trademarks may be owned by Drägerwerk AG & Co. KGaA (Dräger) or its affiliates in certain countries and not necessarily in the country in which this material is released. Visit www.draeger.com/trademarks for the current status of Dräger's trademarks.

Corporate Headquarters

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
■ www.draeger.com

USA

Draeger, Inc.
7256 S. Sam Houston Parkway W.,
Suite 100
Houston, TX 77085
☎ 1 800 4DRAGER
(1 800 437 2437)

Canada

Draeger Safety Canada, Ltd.
2425 Skymark Ave., Unit 1
Mississauga, Ontario L4W 4Y6
☎ 1 877 DRAGER1
(1 877 372 4371)



Locate your Regional Sales
Representative at:
www.draeger.com/contact